

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vklopni ventil »multifix« z nastavljivim gumbom Vel. 5G 3/4

Kategorija: [Start-up valves](#)
Šifra: **100628RIE**

Kratek opis

Start up valve »multifix«, with adjustable throttle, Size 5, G 3/4, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.

The full cross-section of the regulator is opened at 50% of the input pressure.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Ohišje	Aluminium
Serijska	multifix
Tesnilo	NBR
Min. vhodni tlak [bar]	2
Velikost	5
Max. vhodni tlak [bar]	16
D [mm]	52.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	99.7
B [mm]	104.0
Pretok [l/min]	16000