

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## **Vtična cev za nastavke DN6Med. 2.0402zunanja cev Ø 10 mmdolž. 11**

Kategorija: [Plug pipe DN 5 and 6, without shut-off valve](#)  
Šifra: **107942RIE**

### **Kratek opis**

Plug nipple pipe DN 6, Brass 2.0401, Pipe exterior Ø 10 mm, AF 11, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

### **Tehnične Specifikacije**

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Brass 2.0401            |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| O.D. cev [mm]                | 10                      |
| a/f [mm]                     | 11                      |
| Max. obratovalni tlak [bar]  | 15                      |
| Dolžina [mm]                 | 120.0                   |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |