

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Vtični-L fitting »blue serija« dolgi, vrtljivi, R 3/8 o.

Kategorija: [Male elbow, long, swivel type, conical ET, coated](#)  
Šifra: **135644RIE**

(slika je simbolična)

### Kratek opis

Push-in L-fitting »Blue Series« long, rotating, R 3/8 o., for hose exterior Ø 14 mm, pmax short term 15 bar  
Push-in fittings series manufactured in plastic and nickel-plated brass.

All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

### Tehnične Specifikacije

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Min. temperaturno območje [°C]         | -20                                                |
| Min. delovni tlak [bar]                | -0.95                                              |
| Material                               | Plastic and nickel-plated brass                    |
| Navoj                                  | R 3/8                                              |
| Priporočena cev                        | PU or PA (nylon)                                   |
| Rokav                                  | Plastic                                            |
| Serija                                 | Blue series                                        |
| Srednje                                | Compressed air, neutral and safe gases and liquids |
| Tesnilo                                | NBR                                                |
| Max. delovni tlak [bar]                | 10                                                 |
| Za cevi O.D. [mm]                      | 14                                                 |
| Max. working pressure short term [bar] | 15                                                 |
| a/f [mm]                               | 20                                                 |
| L1 [mm]                                | 33.3                                               |
| L2 [mm]                                | 60.2                                               |
| Max. temperaturno območje [°C]         | 80                                                 |