

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vtični L nast., vrtljiv, G 1/4 , zun. premera 6 mm

Kategorija: [Run tee, swivel type, parallel male thread, O-ring](#)
Šifra: **110383RIE**

Kratek opis

Push-in L-fitting, rotating, G 1/4 o., for hose exterior Ø 6 mm, Working pressure max. 15 bar, Stainless steel 1.4404
For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	Stainless steel 1.4404
Navoj	G 1/4
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	DIN EN ISO 228-1
Za cevi O.D. [mm]	6
Delovni tlak pulzira [bar]	10
Max. delovni tlak [bar]	15
a/f [mm]	16
L2 [mm]	20.0
L1 [mm]	21.5
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150