

Datum: 10.05.2024

**Davčna št.:** SI 56119488  
**Telefon:** 01 500 14 42  
**E-mail:** [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
**WWW:** [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Vtični T-okovja »Click-klak«, vrtljivi, G 1/8 o.

Kategorija: [Male branch tees, angled plug connections](#)  
Šifra: **108690RIE**

### Kratek opis

Push-in T-fitting »click-clock«, rotating, G 1/8 o., for hose exterior Ø 4, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Navoj                         | G 1/8               |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za cevi O.D. [mm]             | 4                   |
| a/f [mm]                      | 12                  |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 18.6                |
| L2 [mm]                       | 37.7                |
| Max. delovna temperatura [°C] | 80                  |