

Datum: 12.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Zaporni ventil manometra, puša-puša, svetla medenina, G 1/2

Kategorija: [Wika](#)  
Šifra: **102643RIE**

### Kratek opis

Block valve pressure gauge, Bushing - Bushing, made of bright brass, G 1/2, PN 25 bar, AF 27, max. 50 °C  
It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe.  
When the lever is set to the »blow out« position, the medium is discharged into the atmosphere.  
Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

### Tehnične Specifikacije

|                                |                                                              |
|--------------------------------|--------------------------------------------------------------|
| Aplikacije                     | For all pressure gauges with a flat gasket acc. to DIN 16258 |
| Navoj                          | G 1/2                                                        |
| Ohišje                         | Brass with a bare metal surface                              |
| Različica                      | female / female                                              |
| Ročica                         | Plastic                                                      |
| Standard                       | DIN 16261-A                                                  |
| PN [bar]                       | 25                                                           |
| a/f [mm]                       | 27                                                           |
| Max. temperaturno območje [°C] | 50                                                           |