

Datum: 12.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Zaščitna spojka s tipko s cevnim priklj. I.D.6,ISO6150C,Fi8

Kategorija: [Pushbutton safety coupling DN 6, male, hose stem](#)
Šifra: **141935RIE**

Kratek opis

Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, Sleeve I.D.8, Operating pressure max. 12 bar, Temp. -20°C to 200°C

High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling.

After a second push the plug is released.

This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded.

The safety version meets ISO standard DIN EN ISO 4414.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Gumb	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Navojni kos	Galvanised steel
Ohišje	Stainless steel
Povezava	I.D. 8
Tesnilo	FKM
Ventil	Brass
Vtični profil	acc. ISO 6150 C
Vzmet	Stainless steel
DN	6
Max. obratovalni tlak [bar]	12
a/f [mm]	20
Dolžina [mm]	71.0
Max. temperaturno območje [°C]	200
Pretok	1150 l/min (air)